

# 5W Wall Mount Power Supply Adapter



## ■Features:

- Small low profile package
- No-load consumption<0.1W , Meet DOE VI
- Isolation level: Class II
- Protections: Short circuit/Overload/Overvoltage
- RoHS、 Reach compliance
- LED indicator function optional
- Hi Anti-thunder, Hi ESD protection, Hi-Rel

## ■Application:

- Ethernet devices
- Portable tool
- Audio, Video player
- STB, Network devices
- Charger/PD charger

## ■Description:

The F05L5 series model is a wall-mounted power adapter with a plastic shell design, which can effectively prevent users from electrical hazards. Its working efficiency meets the latest energy efficiency requirements. It can work safely and effectively in an ambient temperature of 0℃ to 40℃. It has complete protection function and is also in line with the relevant certification of electronic information & audio and video (IEC60950, IEC62368). It uses 5W shell, and 26# wire to be compatible with level 5 or 6 energy efficiency. The lightning strike meets 4KV. EMC is designed with Y-cap.

## Key Spec.

MODEL		F05L5-050100SP	F05L5-120050SP
Output	DC Voltage	5V	12V
	Rated Current	1A	0.5A
	Current Range	0 ~ 1A	0 ~ 0.5A
	Rated Power	5W	6W
	Ripple & Noise (max.)remark 2	50mVp-p	120mVp-p
	Voltage regulation rage	4.75 ~ 5.25V	11.4 ~ 12.6V
	Voltage accuracy remark 3	±5.0%	±5.0%
Input	Voltage range	90 ~ 264VAC(277VAC accessible, compatible with 300VAC in India high	
	Frequency range	47 ~ 63Hz	
	Efficiency(Typ.)	73.62%	78.88%
Safety	Safety Standards	IEC/EN60950、 62368	
	Safety type	“●”Indicates that it is currently certified, “◎”Indicates that the applicant meet the certification requirement but not	
	CB	●	●
	CE+LVD	●	●
	BIS	●	●
	UL/CUL	●	●
	GS	●	●
	PSE	●	●
	PSB	◎	◎
	CCC	●	●
	RCM	●	●
	BSMI	●	●
	IRAM	●	●
	KC	●	◎
	SABS	◎	◎
	SASO	◎	◎
	EAC	◎	◎
B-MARK	◎	◎	
SII	◎	◎	
BR	◎	◎	

# 5W Wall Mount Power Supply Adapter

## Electric Spec.

MODEL		F05L5-050100SP	F05L5-120050SP		
Output	DC Voltage	5V	12V		
	Rated Current	1A	0.5A		
	Current Range	0 ~ 1A	0 ~ 0.5A		
	Rated Power	5W	6W		
	Ripple & Noise (max.) <small>remark 2</small>	50mVp-p	120mVp-p		
	Voltage regulation rage	4.75 ~ 5.25V	11.4 ~ 12.6V		
	Voltage accuracy <small>remark 3</small>	±5.0%	±5.0%		
	linear adjustment rate	±1.0%	±1.0%		
	Load Stability	±3.0%	±3.0%		
	Start and rise time	2000ms, 80ms/230VAC 3000ms, 80ms/115VAC(Full load)			
Retention time(Typ.)	20ms/230VAC 10ms/115VAC(Full load)				
Input	Voltage range	90 ~ 264VAC(277VAC accessible, compatible with 300VAC in India high			
	Frequency range	47 ~ 63Hz			
	Stand-by power consumption	100mW	100mW		
	Efficiency(Typ.)	73.62%	78.88%		
	AC current(Typ.)	0.2A max @100~240\	0.2A max @100~240Vac		
	(Typ.) Surge(Typ.) current	COLD START 30A/100Vac 40A/240Vac	COLD START 30A/100Vac 40A/240Vac		
Protection	Overload	110~145% rated output power Hiccup mode: output voltage <50%, recovers automatically after fault condition is removed. Constant current mode: output 50%<voltage < 100%, recovers automatically			
	Overvoltage	7.5 ~ 10V	18 ~ 24V Protection Type: Turn off the output, through the PWM control chip built-in VDD voltage clamping		
Environment	Working TEMP.	0~+40℃ (45℃ can work)			
	Working Humidity	20 ~ 95% RH, non-condensing.			
	Storage Temp.& humidity	-20 ~ +75℃, 20 ~ 95% RH, non-condensing			
	Temperature coefficient	±0.03%/℃ (0~50℃)			
	Vibration resistance	10 ~ 500Hz, 1G 10min/cycle, X, Y, Z 30min for each			
	Operating altitude	5000 meter			
	Withstand voltage(Hi-Pot)	I/P-O/P:3KVAC			
	Insulation resistance	I/P-O/P:100M Ohms / 500VDC / 25℃/ 70% RH			
Electromagnetic compatible	Electromagnetic compatible emission	Parameter	Standard	Test Level / Note	
		Conducted	EN55032(CISPR32), FCC Part 15B	Class B	
		Radiated	EN55032(CISPR32), FCC Part 15B	Class B	
		Harmonic Current	EN61000-3-2	Class A	
	Voltage Flicker	EN61000-3-3	-----		
	Electromagnetic compatibility immunity	EN55035, EN61000-6-2, EN61204-3			
		Parameter	Standard	Test Level /Note	
		ESD	EN61000-4-2	Level 3, 15KV air; Level 2, 8KV	
		Radiated	EN61000-4-3	Level 3, criteria A	
		EFT/Bursts	EN61000-4-4	Level 3, criteria A	
Surge		EN61000-4-5	Level 4, 4KV/L-N, criteria A		
Conducted		EN61000-4-6	Level 3, criteria A		
Magnetic Field	EN61000-4-8	Level 4, criteria A			
Voltage Dips and interruptions	EN61000-4-11	>95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250			
Other	MTBF	≥100K hrs. MIL-HDBK-217F (25℃)			
	Size (W*H*D)	52*38*27mm			
Remark	<p>1., All specifications and parameters shall be measured at the input of 230VAC, rated load and ambient temperature of 25℃ unless otherwise specified.</p> <p>2. Ripple and noise measurement method: capacitance of 0.1uF and 47uF in parallel at the terminal and the measurement is performed under the 20MHZ bandwidth.</p> <p>3. Accuracy: includes setting error, linear adjustment rate and load adjustment rate.</p> <p>4. The power supply adapter is an independent component, but the final adapter still needs to be confirmed in connection with the electromagnetic compatibility of the terminal equipment.</p>				