

ODM / Pure Customization

Lighting Technology for the critical Conditions



- Allow operating temperature : -50°C to 70°C
- Highest rating IP69K protection : Against dust and powerful jet water , underwater 20 meters
- Easy maintenance and reduce failures : DC-In design , DC power can extend to 100m distance
- Durable : Robust pc optical cover , resistant corrosion aluminum housing
- Use high quality NICHIA chip
- Flexible mounting : Adjustable brackets can be positioned and angled
- Customized lighting simulation and design

心型防水燈

Heart Shape Waterproof Light



保護等級 IP69K

允許環境溫度達 70 °C

耐腐蝕

耐高壓水清洗

鋁合金外殼無鳍片設計

PC 透光罩可耐尖端敲擊

Protection rating IP69K

Allow ambient temperature to 70 °C

Resistant corrosion

Against powerful jet water cleaning

Aluminum housing without heat sink

PC optical cover against peak impacts

高溫食品加工廠 Food Processing Factory



陽極處理工廠 Surface Treatment Factory



光生物反應燈

Photosynthetic Light



保護等級 IP69K

Protection rating IP69K

水深 20 公尺

Waterproof up to 20 meters

淨化水質及調整水值 Purify and stabilize the water quality

促進水中藻類穩定生長及生態平衡。

Promote algae growing normally and create an balance environment

水產養殖廠 Aquaculture Factory



耐高溫燈

High Temperature Light



保護等級 IP65

允許環境溫度達 70 °C


PC 透光罩可耐尖端敲擊

Protection rating IP65

Allow ambient temperature to 70 °C

PC optical cover against peak impacts

鑄造工廠
Casting Industry



**冷凍燈
Freezing Light**



保護等級 IP69K
允許環境溫度達負 50°C
耐腐蝕
無冷凝效果

Protection rating IP69K
Allow ambient temperature to -50°C
Resistant corrosion
Work without condensing

**超低溫冷凍倉儲
Freeze Warehouse**



-25°C




-60°C



height of 25meters -40°C

**低溫食品加工處理廠
Frozen Foods Factory**



戶外投射燈 Flooding Light



景觀造景燈 Ecological Landscape Light



食品廠驅蟲照明 波長：1800K

Insect Repellent Light



品名 / Production Name	LED 冷凍燈 / Freezing Light	LED 高溫燈 / High Temperature Light		LED 心型防水燈 / Heart Shape Waterproof Light					
		單鎗 / Single	三鎗 / 3 Units	單鎗 / Single	單鎗 / Single	單鎗 / Single	三鎗 / 3 Units	三鎗 / 3 Units	
型號 / Type	FLFI05701	FLHTC057G01	FLHTC057G03	NJAMG01S	NJBMG05701	NJCM05701	NJBG05703	NJC05703	
LED晶片製造商 / LED Chip Maker	日亞化 / NICHIA	日亞化 / NICHIA	日亞化 / NICHIA	日亞化 / NICHIA	日亞化 / NICHIA	日亞化 / NICHIA	日亞化 / NICHIA	日亞化 / NICHIA	
消耗功率 / Power Consumption	28W	28W	90W	28W	28W	28W	90W	95W	
色溫 / Color Temperature	5700K 白光 / White Light	5700K 白光 / White Light	5700K 白光 / White Light	3000K 黃光 / Warm Light	5700K 白光 / White Light	5700K 白光 / White Light	5700K 白光 / White Light	5700K 白光 / White Light	
輸出光通量 / Output Lumens	2750.9Lm	2733Lm	8932Lm	2058 Lm	2733Lm	2687Lm	8932Lm	10156Lm	
發光效率 / Luminous Efficacy	108.7Lm/W	101.2Lm/W	110.4Lm/W	77.9Lm/W	101.2Lm/W	114.3Lm/W	110.4Lm/W	116.2Lm/W	
燈具效率 / Lumininaire Efficiency	90.64m/W	84.3m/W	99.9Lm/W	63.49m/W	84.3m/W	95.5Lm/W	99.9Lm/W	106.7Lm/W	
輸入電壓 / Input Voltage	100-277 Vac.	100-277 Vac.	100-277 Vac.	100-277 Vac.	100-277 Vac.	100-277 Vac.	100-277 Vac.	100-277 Vac.	
尺寸 / Dimension (mm)	L: 390 / W: 79 / H: 52	L: 590 / W: 51 / H: 34	L: 590 / W: 150 / H: 80	L: 590 / W: 59 / H: 53	L: 590 / W: 59 / H: 53	L: 590 / W: 59 / H: 53	L: 590 / W: 185 / H: 100	L: 590 / W: 185 / H: 100	
操作溫度 / Operation Temperature	-50°C ~ 40°C	-25°C ~ 70°C	-25°C ~ 70°C	-25°C ~ 50°C	-25°C ~ 50°C	-30°C ~ 50°C	-25°C ~ 50°C	-30°C ~ 50°C	
壽命 / Lifetime	40,000 hrs	40,000 hrs	40,000 hrs	40,000 hrs	40,000 hrs	40,000 hrs	40,000 hrs	40,000 hrs	
重量 / Weight (不含Power)	1491g	954g	2927g	1400g	1348g	1359g	2250g	4101g	
演色性 / CRI	≥70~80Ra	≥70~80Ra	≥70~80Ra	≥70~80Ra	≥70~80Ra	≥70~80Ra	≥70~80Ra	≥70~80Ra	
發光角度 / Beam Angle	68.15°	64.4°	62.5°	64.55°	64.4°	63.6°	62.5°	26.8°	
防護等級 / Protection Class	IP 69K	無防水	無防水	IP 69K	IP 69K	IP 69K	IP 69K	IP 69K	
主體材質 / Housing Material	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	鋁合金 / Aluminum Alloy	
PC透光罩 / PC Optical Cover	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	厚度 / Thickness:3 mm	
散光膜 / Diffuser Film	有 / With	有 / With	沒有 / Without	有 / With	有 / With	有 / With	沒有 / Without	沒有 / Without	
抗腐蝕 / Anti-Corrosion	Customize	Customize	Customize	Customize	Customize	Customize	Customize	Customize	
可調整安裝支架 / Adjustable Mounting	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
適用場所 / Application Location	冷凍庫 / Freezer	熱處理廠/玻璃廠/鑄造廠 Heat treatment factory / Glass factory / Casting		戶外/水底/食品加工廠/屠宰場/陽極處理廠 Outdoor / Underwater / Foods factory / Slaughterhouse / Surface treatment factory...etc					

創芯綠能有限公司
CHUANG-HSIN Greenergy Co.,Ltd.
頂極科技股份有限公司

