

65W(GaN) USB C Charger



■ Features:

- Miniaturized Design: Small size and light weight
- No-load consumption < 0.1W, Meet DOE VI
- Support protocols: PD@PPS, QC, FCP, SCP
- Protections: Short circuit / Overload / Overvoltage / OverTemperature
- RoHS, Reach compliance

■ Application:

- Mobile Phone
- Tablet
- NoteBook
- Digital Product (USB-C Charge)

■ Description:

The FC065X series model is a USB C charger with a plastic shell design, which can effectively prevent users from electrical hazards. Its efficiency meets the latest energy efficiency requirements. It can work safely and effectively at an ambient temperature of 0°C to 40°C. It has complete Protection function and compliance with electronic information & audio and video (IEC60950, IEC60065, IEC62368) related certifications, compatible with PD&PPS, QC, FCP, SCP and other protocols, enabling quick charging of mobile phones and tablet products.

Key Specification

Model	FC065P02-200033C	
Output	Voltage	5V3A/9V3A/12V3A/15V3A/20V3.25A
	Protocol	PD3.0/PPS/FCP/SCP/QC2.0/QC3.0
	Ripple&Noise(pk-pk)	300Vp-p
Input	Voltage range	90 ~ 264VAC
	Frequency range	47 ~ 63Hz
	Efficiency(Typ.)	88%
Safety	Safety standards	IEC/EN60950、60065、62368
	Safety Type	“●” Indicates that it is currently certified, “◎” Indicates that the applicant meet the certification requirement but not be certified
	CB	◎
	CE+LVD	◎
	BIS	◎
	UL/CUL	◎
	GS	◎
	PSE	◎
	PSB	◎
	CCC	◎
	RCM	◎
	BSMI	◎
	IRAM	◎
	KC	◎
	SABS	◎
	SASO	◎
EAC	◎	
B-MARK	◎	
SII	◎	
BR	◎	

65W(GaN) USB C Charger

Electrical Specification

Model		FC065P02-200033C			
Output	Voltage	5V3A/9V3A/12V3A/15V3A/20V3.25A			
	Protocol	PD3.0/PPS/FCP/SCP/QC2.0/QC3.0			
	Ripple&Noise(pk-pk)	300Vp-p			
	Start and Rise time	3000ms, 80ms/230VAC			
Input	Voltage range	90 ~ 264VAC			
	Frequency range	47 ~ 63Hz			
	Standby Power	75mW			
	Efficiency(Typ.)	88%			
	Input current(Typ.)	1.8A max @100~240Vac			
	Surge current(Typ.)	COLD START 60A/100Vac 100A/240Vac			
Protection	OverLoad	140% max of rated output current			
		Recovers automatically after fault condition is removed			
	Overvoltage	27Vmax	Protection Type: Turn off the output, through the PWM control chip built-in VDD voltage clamping		
Environment	Operating Temperature	0~ +40°C			
	Operating Humidity	20 ~ 85% RH, non-condensing			
	Storage Temperature&Humidity	-20 ~ +75°C, 5 ~ 95% RH, non-condensing			
	Temperature coefficient	±0.03%/°C (0~ 50°C)			
	Vibration resistant	10 ~ 500Hz, 1G 10min/circle, X, Y, Z 30mins for each			
	Altitude	2000m			
	Withstande voltage	I/P-O/P:3KVAC			
	Isulation resistant	I/P-O/P:100M Ohms / 500VDC / 25°C/ 70% RH			
EMC	EMI	Parameter	Standard	Test Level / Note	
		Conducted	EN55032(CISPR32), FCC Part 15B	Class B	
		Radiated	EN55032(CISPR32), FCC Part 15B	Class B	
		Harmonic	EN61000-3-2	Class A	
		Voltage	EN61000-3-3	-----	
	EMS	EN55035, EN61000-6-2, EN61204-3			
		Parameter	Standard	Test Level /Note	
		ESD	EN61000-4-2	Level 3, 15KV air; Level 2,	
		Radiated Susceptibility	EN61000-4-3	Level 3, criteria A	
		EFT/Burest	EN61000-4-4	Level 3, criteria A	
		Surge	EN61000-4-5	Level 4, 4KV/L-N, criteria A	
		Conducted	EN61000-4-6	Level 3, criteria A	
		Magnetic Field	EN61000-4-8	Level 4, criteria A	
Voltage DIPS and interruptions	EN61000-4-11	>95% DIP 0.5 periods, 30% DIP 25 periods, >95% interruptions 250 periods			
Others	MTBF	≥100K hrs. MIL-HDBK-217F (25°C)			
	Size(W*H*D)	63.5*46.5*28mm			
Remark	<p>1. All specifications and parameters shall be measured at the input of 230VAC, rated load and ambient temperature of 25°C unless otherwise specified.</p> <p>2. Ripple and noise measurement method: capacitance of 0.1uF and 47uF in parallel at the terminal and the measurement is performed under the 20MHZ bandwidth.</p> <p>3. Accuracy: includes setting error, linear adjustment rate and load adjustment rate.</p> <p>4. The power supply adapter is an independent component, but the final adapter still needs to be confirmed in connection with the electromagnetic compatibility of the terminal equipment.</p>				